

B-MODS

1 – WEIGHT:

GM602 and Quicksilver 602 SEALED CRATE MOTOR.....2400lbs after race w/driver

OPEN MOTOR360ci or Less 2400lbs after race w/driver

361ci or More 2450lbs after race w/driver

Must Add 50lbs for Bert, Brinn or Falcon Transmission

****4-Bar Cars must add 100lbs****

2 – ENGINES:

Cast Iron Block & Heads ONLY! No Aluminum Blocks or Heads Allowed!

NO Roller Camshafts or Rev-Kits will be Allowed!

NO Dry Sump Oil Systems

NO Altering or Machining on the outside of Engine Block, Heads or Intake

NO Tri-Y or Square Tube Headers!

3 – CARBURETORS:

Gauge Legal Holley 4412 500 2-Barrel - NO AEROSOLS or SUPERBOWLS will be Allowed!

HP or XP Carburetors Will Not Be Allowed!

ALL PARTS MUST REMAIN STOCK, NO GRINDING OR POLISHING OF ANY KIND!

Choke Horn may be removed

Aftermarket Metering Block will be Allowed

Willy's Rollover Plate will be Allowed!

Holley 80541-1 650 4-Barrel on Crate Motor ONLY!

4 – FUEL:

PUMP GAS, E-85, Alcohol or Race Gas!

NO Nitrous or Fuel Additives of any kind Allowed!

5 - FUEL CELL:

Contained fuel cells only, fuel cells to be securely mounted in rear, using minimum (2) 2"x 1/8"

flat steel straps or minimum 1" square tube & 3/8" bolts . NO PICKUP TUBES or FITTINGS

OF ANY KIND ALLOWED ON THE SIDE OF THE FUEL CELL!

6 - FIRE EXTINGUISHER:

All cars to be equipped with a filled, operable fire extinguisher securely mounted within reach of the driver.

7 - TIRES & WHEELS:

Any 8 inch mod tire

Grooving & Siping will be Allowed!

NO Altering Allowed Softening or Chemical! Any Steel Wheel 8" MAXIMUM, Beadlocks will be Allowed on the Right Side ONLY!

8 – REARENDS & DRIVESHAFT:

Quickchange Rarends will be allowed,

DRIVESHAFTS MUST BE STEEL, NO ALUMINUM or CARBON FIBER!

9 – SHOCKS/BUMP STOPS/BUMP SPRINGS:

ANY STEEL SHOCK WILL BE ALLOWED, NO EXTERNAL ADJUSTABLE, BULB-TYPE or SCHRADER VALVE SHOCKS will be ALLOWED! NO BUMP STOPS, BUMP SPRINGS or SPRING RUBBERS of ANY KIND ALLOWED at ANYTIME!

\$100 CLAIM ON ANY SHOCK AT ANYTIME!

10 – BODIES & CHASSIS:

A 5" Rear Spoiler will be Allowed

Left Side Door to Firewall must be Enclosed!

ALL OTHER BODY & CHASSIS RULES WILL BE THE SAME AS THE BASIC UMP A-MOD RULES!

LOWER A-FRAMES MUST BE STOCK LENGTH NO EXCEPTION'S!